
## Control4® EA-3 Controller



## Control4® EA-3 Entertainment and Automation Controller C4-EA3, C4-EA3-V2

The versatile Control4 EA-3 Entertainment and Automation Controller is the perfect fusion of multi-room, high-resolution audio and smart home automation for small to mid-size homes.

Powered by a next-generation multi-core processor, the EA-3 delivers a new level of speed and performance for instantaneous, interactive on-screen access to all the systems in the home. A built-in music server with three audio outputs delivers high-resolution audio throughout the home from your local music library, popular streaming music services, and AirPlay-enabled devices using native Control4 ShairBridge technology.

The EA-3 includes a variety of I/O to automate audio and video, lighting, climate control, door locks, and other devices controlled by IP, infrared (IR), serial, and ZigBee. With PoE+ for power, a port for Ethernet out, and its optional mounting bracket, the compact form factor of the EA-3 makes it easy to install behind any TV or projector.

- Three audio outputs—one HDMI, one stereo analog, and one digital coax—distribute up to three simultaneous, high-resolution audio streams from native streaming services, AirPlay-enabled devices, and local music.
- Integrated music server with native support for popular streaming services, including Deezer, Pandora, Rhapsody, Tidal, and TuneIn.
- Elegant on-screen experience for easy access to entertainment and the entire home.
- · Low-profile design features an integrated power supply for flexible, simple installation and long-term reliability.
- PoE+ provides power and network connectivity over a single CAT5/CAT6 cable.
- Built-in two-port Ethernet switch simplifies installation by connecting an additional device to the home network.
- · Optional mounting bracket allows easy mounting to the back of your TV, on the wall, or to a standard wall box.
- Integrated ZigBee radio with external antennas simplify installation while delivering high-performance connectivity.
- USB port enables connection to external hard drives for easy access to music content.
- Control4 App license enables in-home control from multiple iOS—including Apple Watch—and Android mobile devices. Connect to your home remotely with an optional 4Sight subscription.
- Video/Audio Intercom for whole-home communications with Control4 touch screens and door stations.











@DTIColombiaSAS **f** 



## **ESPECIFICACIONES**

## Control4® EA-3 Controller

| Entertainment and Automation Controller, 3 Zone  | C4-EA3   |
|--|--|
| Entertainment and Automation Controller, 3 Zone, | C4-EA3-V2  |
| V2   | 04 E/10 V2   |
|  | Embedded services  |
| Control4 App license                             | Included—Supports up to 50 devices   |
| Streaming services                               | Pandora*, Napster*, Spotify, TuneIn, TIDAL, Deezer   |
| ShairBridge                                      | Up to 20 instances of the driver in the project; 3 concurrent stream   |
|  | Inputs/outputs   |
| Video out  | 1 video out—HDMI   |
| Video  | HDMI 1.4 output; HD 1080p, 50-60 Hz  |
| Audio out  | 3 audio out—1 HDMI, 1 stereo analog (3.5 mm), 1 digital coax   |
| Audio in   | 2 audio in—1 stereo analog (3.5 mm), 1 digital coax  |
| Audio playback formats                           | AAC, AIFF, ALAC, FLAC, M4A, MP2, MP3, MP4/M4A, Ogg Vorbis, PCM, WAV, WMA   |
| High-resolution audio playback                   | Up to 192 kHz / 24 bit   |
| Advanced audio subsystem                         | Dedicated audio signal processor   |
| Audio system controls (analog only)              | 10-band graphic equalizer, input gain, output gain, loudness, tone controls, balance                                 |
| Signal-to-noise ratio                            | <-110 dBFS   |
| Total harmonic distortion                        | 0.0015 (-96.5 dB)  |
|  |  |
| Ethernet   | 10/100/1000BaseT compatible (required for controller setup) PoE-supported  |
| Power over Ethernet                              | 802.3at-2009 (PoE+) / 25.5W  |
| Built-in Ethernet switch                         | 1 Ethernet/PoE in + 1 Ethernet switch port   |
| WiFi   | Internal Dual-Band Wireless-N (EA-3 V1)  |
|  | (2.4 GHz, 5 GHz, 802.11n/g/b)<br>Optional Dual-Band WiFi USB Adapter (EA-3 V2)<br>(2.4 GHz, 5 Ghz, 802.11ac/b/g/n/a) |
| WiFi security                                    | WPA/WPA2   |
| WiFi antenna                                     | External reverse SMA connector (EA-3 V1 only); optional WiFi adapter on the EA-3 V2                                  |
| ZigBee Pro                                       | 802.15.4   |
| ZigBee antenna                                   | External reverse SMA connector   |
| USB port   | 1 USB 2.0 port-500mA   |
|  |  |
| IR out   | 6 IR out—5V 27mA max output, 1 IR blaster—front  |
| IR capture                                       | 1 IR receiver—front; 20-60 kHz   |
| Serial out                                       | 3 serial out (shared with IR out 1-3)  |
| Contact  | 1 contact sensor—2V-30VDC input,<br>12VDC 125mA maximum output   |
| Relay  | 1 relay—AC: 36V, 2A maximum voltage across relay;<br>DC: 24V, 2A maximum voltage across relay                        |
|  | Power  |
| Power requirements                               | 100-240 VAC, 60/50 Hz or PoE+  |
| Power requirements  Power consumption            | Max: 25W, 85 BTUs/hour; Idle: 13W, 44 BTUs/hour  |
| rower consumption                                | Other  |
| Operating temperature                            | 0 ~ 40 °C (32 ~ 104 °F)  |
| Storage temperature                              | -20 ~ 70 °C (4 ~ 158 °F)   |
| Fan dB level                                     | Max: 35 dB   |
| Dimensions (H × W × D)                           | 31 mm (1.25") × 221 mm (8.75") × 149 mm (5.875")   |
| Weight   | 0.74 kg (1.60 lb)  |
| Shipping weight                                  | 1.26 kg (2.75 lb)  |
|  | al accessories (not included)  |
| Wall-Mount Bracket                               | C4-WMEA3   |
| Rack-Mount Kit                                   | C4-EA3RMK1, C4-EA3RMK2   |
| 3.5 mm to DB9 Serial Cable                       | C4-CBL3.5-DB9B   |
|  | C4-CBL3.3-DB9B<br>C4-SR260-B   |
| SR-260 System Remote Control                     |  |



